

Xerox[®] VersaLink[®] B400 Printer

VersaLink® B400 Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK® B400
One-sided Speed ¹ 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 47 ppm black-and-white Up to 45 ppm black-and-white Up to 38 ppm black-and-white
Two-sided Speed ¹ 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 29 ppm black-and-white Up to 28 ppm black-and-white Up to 25 ppm black-and-white
Monthly Duty Cycle ²	Up to 150,000 pages / month
Recommended Average Monthly Print Volume ³	Up to 15,000 pages
Processor	1.05 GHz Dual Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS						
ELECTRICAL REQUIREMENTS						
North America	Voltage: 110-127 VAC Frequency: 50/60 Hz 11	A				
Europe and Other Geographies	Voltage: 220-240 VAC Frequency: 50/60 Hz 6 A					
POWER CONSUMPTION						
Continuous Printing ⁴	565 watts or less					
Ready (Standby) ⁴	46 watts or less					
Energy Saver (Sleep Mode) ⁴	4 watts or less					
OPERATING ENVIRONMENT						
Required Temperature Range (Storage)	32 to 95° F / 0 to 35° C					
Required Temperature Range (Operating)	50 to 90° F / 10 to 32° C					
Required Relative Humidity	10 % to 85 %	10%to 85%				
Sound Power Levels Operating Standby	7.5 B(A) or less 5.3 B(A) or less					
Sound Pressure Levels Operating Standby	56 dB(a) or less 30 dB(a) or less					
Boot Time (from Off to UI Ready)	As fast as 60 seconds					
Warm-up Time (from Sleep to UI Ready)	As fast as 5 seconds					
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH		HEIGHT		WEIGHT
VersaLink® B400	18.1 in. / 459 mm	16.8 in. / 4	426 mm	13.3 in. / 339 mi	m	30 lb. / 14 kg
550-sheet Paper Tray	15.5 in. / 393 mm	15.5 in. / 3	393 mm	3.7 in. / 94 mm		7 lb. / 3.2 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH		HEIGHT		WEIGHT
VersaLink® B400	21.3 in. / 540 mm	23.1 in. / 5	588 mm	21.7 in. / 480 mi	m	38.3 lb. / 17.35 kg
550-sheet Paper Tray	19.6 in. / 498 mm	19.8 in. / 5	504 mm	9.2 in. / 234 mm	I	9.6 lb. / 4.4 kg
SYSTEM CERTIFICATION/REGULA						
Certifications	To view the latest list of	certifications	s, go to www.xe	erox.com/OfficeCe	rtificatio	ns.
PRINT						
First-Print-Out Time	As fast as 4.7 seconds					
Print Resolution	Up to 1200 x 1200 dpi (6	enhanced)			1	
Page Description Languages	PCL® 5e, 6 PDF XPS		TIFF JPEG		HP-GL Adobe®	PostScript® 3™
Maximum Print Area	4 mm from edge of paper					
Print Features	Application Defaults					

Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Fonts	PostScript fonts: 136 PCL fonts: 83
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A
	Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing Watermark (predefined and custom) Xerox® Earth Smart Driver Settings

SOFTWARE SOLUTIONS	
Xerox® ConnectKey Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey Technology-enabled device.
MOBILE SOLUTIONS AND MOBIL	LE DEVICE APPS
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopriα [®] Certified	ConnectKey Technology-enabled MFPs are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox [®] @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Services plug-in for Android devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud-based version (Workplace Cloud) of this solution.
SECURITY	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)

ACCOUNTING			
XEROX® STANDARD AC	COUNTING TOOL/NETWORK ACC	OUNTING (STANDARD)	
Tracking	Print usage		
Accounting	Xerox® Standard Accound Up to 1,000 User Accound Up to 9,999 User Accound Up to 500 General Accounting (Journ Louis) Up to 1,000 User IDs; Up to 60,000 User IDs; Up to 14,000 Accounting	nts without SSD nts with SSD unts b Based Accounting) p to 1,000 Account IDs without SSD Up to 60,000 Account IDs with SSD	
Features	Administrator can mana	age the feature via the Embedded We	eb Server.
ACCOUNTING OPTIONS	S – NETWORK ACCOUNTING (ALL	OWS CENTRAL SERVER TO MANA	GE ALL ACCOUNTING)
	 Comprehensive mand Numerous solutions a Security enhancemen Device requests accounaccounts Accept Authentication 	ts include simultaneous support for H	and reporting of print usage artners. For details visit www.xerox.com TTP/HTTPS protocols rver enabling larger databases of users and nird party Networking Account
PAPER HANDLING			
BYPASS TRAY			
Capacity ⁵	150 sheets		
Sizes	Custom sizes: 3 x 5 in. to	8.5 x 14 in. / 76.2 x 127 mm to 216 x	x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cov 16 lb. bond to 60 lb. cov		
Media Types	Bond Plain Paper Cardstock Custom	Envelopes Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled
TRAY 1	1	1	
Capacity ⁵	550 sheets		
Sizes	Custom Sizes: 3 x 5 in. to	o 8.5 x 14 in. / 76.2 x 127 mm to 216 :	x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cov 16 lb. bond to 60 lb. cov		
Mediα Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled
OPTIONAL TRAY 2			·
Capacity ⁵	550 sheets		
Sizes	Custom sizes: 5.5 x 8.3 i	n. to 8.5 x 14 in. / 139.7 x 210 mm to	216 x 356 mm

Weights One-sided: Two-sided:	16 lb. bond to 80 lb. o	cover / 60 to 220 gsm cover / 60 to 163 gsm	
Media Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled
TOTAL CAPACITY ⁵			
Device Standard Capacity ⁵	700 sheets		
Device Total Capacity ⁵	2,350 sheets		
PAPER OUTPUT			
Output Capacity ⁵	250 sheets		
Automatic Two-sided Printing	Standard		
DEVICE MANAGEMENT			
Network Protocols	TCP/IP: HTTP/HTTPS, LDAP Bonjour®/AirPrint® Most protocols not in	-	v Socket Printing/Port 9100, IPv4/IPv6, WSD
Administrative Protocols	DHCP, SNMP, WINS,	HTTP, HTTPS, TLS, SNTP, MDNS	
REMOTE CONTROL PANEL			
	IT administrators a	e convenient technical support and user nd authorized users can control the devi ence is identical to performing tasks dire	ce remotely from a web page on anydevice
XEROX® CENTREWARE® WEB	1		
	management fromWorks with any SNIProvides help with a	MP-managed printer from any manufac	ows or UNIX or any other operating system turer a checks and troubleshooting, and device
EMBEDDED WEB SERVER – INT	EGRATED DEVICE WEB	PAGE	
Device Status	Tray Status / ConteConsumables StatuBilling / UsageQuick LinksOnline Support		
Print Queue Viewing	Job print queue man	agement — view and delete	
Job Submission	Print-ready files (PS, F	PCL, PDF, XPS, JPEG)	
Device Administration	Allows simple, remote	e installation setting of configuration op	tions and management of the device
Browsers	Microsoft® Internet E Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	ixplorer®	

Xerox® VersaLink® B400 Printer

REMOTE SERVICES		
Automated Meter Readings (AMR)	Automates the process of collecting and submitting usage. Eliminates the need for time-consuming end submitted to Xerox on time.	meter reads for tracking and billing of Xerox® device I-user involvement and ensures that meter reads are
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
WHAT COMES IN THE BOX		
	VersaLink® B400 Printer Standard Capacity Toner Cartridge: 5,900 print caps Software and Documentation CD (Safety, Regulator Warranty Statement) Installation Guide Quick Use Guides Power Cord	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
SUPPLIES Standard Capacity Toner Cartridges	5,900 standard pages ⁶	106R03580
Standard Capacity Toner	5,900 standard pages ⁶ 13,900 standard pages ⁶	106R03580 106R03582
Standard Capacity Toner Cartridges	, 3	
Standard Capacity Toner Cartridges High Capacity Toner Cartridges Extra-High Capacity Toner	13,900 standard pages ⁶	106R03582
Standard Capacity Toner Cartridges High Capacity Toner Cartridges Extra-High Capacity Toner Cartridges	13,900 standard pages ⁶ 24,600 standard pages ⁶	106R03582 106R03584
Standard Capacity Toner Cartridges High Capacity Toner Cartridges Extra-High Capacity Toner Cartridges Drum Cartridge	13,900 standard pages ⁶ 24,600 standard pages ⁶	106R03582 106R03584
Standard Capacity Toner Cartridges High Capacity Toner Cartridges Extra-High Capacity Toner Cartridges Drum Cartridge ACCESSORIES / OPTIONS	13,900 standard pages ⁶ 24,600 standard pages ⁶ 65,000 standard pages ⁷	106R03582 106R03584 101R00554
Standard Capacity Toner Cartridges High Capacity Toner Cartridges Extra-High Capacity Toner Cartridges Drum Cartridge ACCESSORIES / OPTIONS 550-sheet Paper Tray	13,900 standard pages ⁶ 24,600 standard pages ⁶ 65,000 standard pages ⁷	106R03582 106R03584 101R00554 497K13620
Standard Capacity Toner Cartridges High Capacity Toner Cartridges Extra-High Capacity Toner Cartridges Drum Cartridge ACCESSORIES / OPTIONS 550-sheet Paper Tray Productivity Kit with 16 GB Solid	13,900 standard pages ⁶ 24,600 standard pages ⁶ 65,000 standard pages ⁷	106R03582 106R03584 101R00554 497K13620 097S04913

¹ Declared print speed in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.
⁵Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
⁶Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/Latest/SUPGL-01.pdf.