

Xerox[®] VersaLink[®] C500 Color Printer

VersaLink® C500 Color Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.



| SYSTEM SPECIFICATIONS | VERSALINK® C500 |
|---|--|
| One-sided Speed ¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm | Up to 45 ppm color and black-and-white Up to 43 ppm color and black-and-white Up to 37 ppm color and black-and-white |
| Two-sided Speed ¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm | Up to 44 ppm color and black-and-white Up to 42 ppm color and black-and-white Up to 22 ppm color and black-and-white |
| Monthly Duty Cycle ² | Up to 120,000 pages/month |
| Recommended Average Monthly Print Volume ³ | Up to 10,000 pages |
| Hard Drive | Optional 320 GB HDD |
| Processor | 1.05 GHz ARM Dual-Core |
| Memory | 2 GB |
| Connectivity | Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair |
| Controller Features | Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support |
| User Interface Languages | English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian |

| ELECTRICAL REQUIREMENTS | | | | | | |
|--|---|-----------------------------|--|------------------|--|--|
| | | | DEVICE SPECIFICATIONS ELECTRICAL REQUIREMENTS | | | |
| North America | Voltage: 110-127V -10 % /+6 % Frequency: 50/60 Hz +/-3 %, 12A | | | | | |
| Europe and Other Geographies | Voltage: 220-240V +/-10 % Frequency: 50 Hz +/-3 %, 8A | | | | | |
| POWER CONSUMPTION | | | | | | |
| Continuous Printing ⁴ | 730 watts or less | | | | | |
| Ready/Standby Mode ⁴ | 74 watts or less | | | | | |
| Energy Saver/Sleep Mode ⁴ | .9 watts or less | | | | | |
| OPERATING ENVIRONMENT | _ | | | | | |
| Required Temperature Range (Storage) | 32° to 95° F (0° to 35° C) | | | | | |
| Required Temperature Range (Operating) | 50° to 90° F (10° to 32° C) | | | | | |
| Required Relative Humidity | 15% to 85% | | | | | |
| Sound Power Levels Operating Standby | 7.17 B(A) or less 4.9 B(A) or less | | | | | |
| Sound Pressure Levels Operating Standby | 56.2 dB(A) or less 33.6 dB(A) or less | | | | | |
| Boot Time (from Off to UI Ready) | As fast as 52 seconds | | | | | |
| Warm-up Time (from Sleep to UI Ready) | As fast as 11 seconds | | | | | |
| DIMENSIONS AND WEIGHT (UNPACKAGED) | WIDTH | DEPTH | HEIGHT | WEIGHT | | |
| VersaLink® C500 | 16.9 in./427.4 mm | 18.4 in./465.5 mm | 17.5 in./443.4 mm | 61 lb./27.6 kg | | |
| 550-sheet Paper Tray | 16.5 in./420 mm | 18.3 in./464.5 mm | 4.8 in./123 mm | 4.1 lb./6.6 kg | | |
| High Capacity Feeder | 28.5 in./724.2 mm | 30.4 in./772.1 mm | 18.1 in./459 mm | 43.4 lb./19.7 kg | | |
| Caster Base | 28.5 in./724.2 mm 30.4 in./772.1 mm 3.5 in./90 mm 18.7 lb./8.5 kg | | | | | |
| DIMENSIONS AND WEIGHT (PACKAGED) | WIDTH DEPTH HEIGHT WEIGHT | | | | | |
| VersaLink® C500 | 22.8 in./580 mm | 25 in./634 mm | 23.9 in./607 mm | 75 lb./34 kg | | |
| 550-sheet Paper Tray | 21.1 in./535 mm 23 in./584 mm 9.8 in./248 mm 18.7 lb./8.5 kg | | | | | |
| High Capacity Feeder | 22.4 in./568 mm 26.1 in./663 mm 28 in./711 mm 83.8 lb./38 kg | | | | | |
| Caster Base | 23 in./585 mm 24.4 in./619 mm 13 in./330 mm 39.7 lb./18 kg | | | | | |
| CERTIFICATIONS | | | | | | |
| | To view the latest list of | certifications, go to www.x | cerox.com/OfficeCertificat | cions. | | |

| PRINT | | |
|----------------------------|--|--|
| First-Print-Out Time | As fast as 5.3 seconds color/5.0 seconds black-and-white | |
| Print Resolution | Up to 1200 x 2400 dpi | |
| Page Description Languages | PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™ | |
| Maximum Print Area | 4 mm from edge of paper | |
| Print Features | Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing Watermark (predefined and custom) Earth Smart Driver Settings | |
| Print from USB | Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A | |
| Operating Systems | Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com. | |
| Fonts | PostScript fonts: 136 PCL fonts: 83 | |

| Xerox® Global Print Driver® | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. | |
|---|--|--|
| Xerox® Pull Print Driver | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others. | |
| MOBILE SOLUTIONS AND MOBI | LE DEVICE APPS | |
| Apple [®] AirPrint [®] | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network. | |
| Mopriα [®] Certified | ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily. | |
| Xerox® @printbyXerox App | @printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel. | |
| Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store) | The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store. | |
| Xerox® Workplace Suite and Xerox® Workplace Cloud | Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution. | |
| SOFTWARE SOLUTIONS | | |
| Xerox® ConnectKey® Apps (Found αt the Xerox® App Gαllery) | Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device. | |

| SECURITY | |
|-------------------------------------|---|
| SECURITY | |
| Security Features | Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM) |
| | *Requires HDD/Productivity Kit |
| ACCOUNTING | |
| XEROX® STANDARD ACCOUNTIN | NG/NETWORK ACCOUNTING (STANDARD) |
| Tracking | Print usage |
| Accounting | Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions) |
| Features | Administrator can manage the feature via the Embedded Web Server. |
| | ORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING) |
| | Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account |
| PAPER HANDLING | |
| BYPASS TRAY | |
| Capacity ⁵ | 150 sheets |
| Sizes | Custom sizes: 3 x 5 in. to 8.5 x 14 in./76 x 127 mm to 216 x 356 mm |
| Weights One-sided: Two-sided: | 16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm |

| Types TRAY 1 | Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Cardstock Pre-Printed Recycled |
|-------------------------------------|--|
| Capacity ⁵ | 550 sheets |
| Sizes | Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76 x 190 mm to 216 x 356 mm |
| Weights One-sided: Two-sided: | 16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm |
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled Envelope |
| UP TO FOUR ADDITIONAL TRAYS | S (OPTIONAL) |
| Capacity ⁵ | 550 sheets |
| Sizes | Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76 x 190 mm to 216 x 356 mm |
| Weights One-sided: Two-sided: | 16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm |
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled |
| HIGH CAPACITY FEEDER (OPTIO | NAL) |
| Capacity ⁵ | 2,000 sheets |
| Sizes | Letter/A4 |
| Weights One-sided: Two-sided: | 16 lb. bond to 65 lb. cover/60 to 176 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm |

| Types | Bond Plain Paper Hole Punched Letterhead Lightweight Cardstock Pre-Printed Recycled | |
|---|--|--|
| TOTAL CAPACITY | | |
| Standard Device Capacity ⁵ | 700 sheets | |
| Total Device Capacity ⁵ | 3,250 sheets | |
| PAPER OUTPUT | | |
| Output Capacity ⁵ | 500 sheets | |
| Automatic Two-sided Printing | Standard | |
| DEVICE MANAGEMENT | | |
| Network Protocols | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled | |
| Administrative Protocols | DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS | |
| REMOTE CONTROL PANEL | | |
| | Enables faster, more convenient technical support and user training IT administrators and other authorized users can control the device remotely from a web page on any device Remote user experience is identical to performing tasks directly at the device | |
| XEROX® CENTREWARE® WEB SO | T | |
| | A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management | |
| XEROX® EMBEDDED WEB SERVE | R – INTEGRATED DEVICE WEB PAGE | |
| Device Status | Tray Status/Contents Consumables Status Billing/Usage Quick Links Online Support | |
| Print Queue Viewing | Job print queue management — view and delete | |
| Job Submission | Print-ready files (PS, PCL, PDF, XPS, JPEG) | |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device | |
| Browsers | Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™ | |
| REMOTE SERVICES | | |
| Automated Meter Readings (AMR) | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. | |
| Automatic Supplies Replenishment (ASR) | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory. | |

| MULATIC IN THE POY | | | |
|---|---|--|--|
| WHAT'S IN THE BOX | | | |
| | VersaLink® C500 Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 2,400 print capacity ⁶ , Black: 5,000 print capacity ⁶ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord | | |
| SUPPLIES AND ACCESSORIES | QUANTITY | PART NUMBER | |
| SUPPLIES | | | |
| Standard Capacity Toner Cartridges | Black: 5,000 standard pages ⁶ Cyan: 2,400 standard pages ⁶ Magenta: 2,400 standard pages ⁶ Yellow: 2,400 standard pages ⁶ | 106R03862 106R03859 106R03860 106R03861 | |
| High Capacity Toner Cartridges | Black 12,100 standard pages ⁶ Cyan: 5,200 standard pages ⁶ Magenta: 5,200 standard pages ⁶ Yellow: 5,200 standard pages ⁶ | 106R03869 106R03863 106R03864 106R03865 | |
| Extra High Capacity Toner Cartridges | Cyan: 9,000 standard pages ⁶ Magenta: 9,000 standard pages ⁶ Yellow: 9,000 standard pages ⁶ | 106R03866 106R03867 106R03868 | |
| ROUTINE MAINTENANCE ITEMS | | | |
| Drum Cartridges | Cyan: 40,000 pages ⁷ Magenta: 40,000 pages ⁷ Yellow: 40,000 pages ⁷ Black: 40,000 pages ⁷ | 108R01481 108R01482 108R01483 108R01484 | |
| Waste Cartridge | 30,000 pages ⁷ | 108R01416 | |
| ACCESSORIES | | | |
| 550-sheet Feeder | | 097S04949 | |
| 2,000-sheet High Capacity Feeder (includes Caster Base) | | 097S04948 | |
| Cabinet (includes stabilisers) | | 097S04994 | |
| Caster Base | | 097S04954 | |
| Productivity Kit with 320 GB HDD | | 497K18360 | |
| Wireless Network Adapter (Wi-Fi Kit) | | 497K16750 | |
| External Card Reader/RFID Kit | | 497K18380 | |

 $^{^{\}rm 1}\,\text{Declared}$ print speed in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴Paper capacities are based on 20 Ib/75 gsm stock; capacities will vary with different weight stocks.

⁵Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁶Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.

⁷Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf.